



TOMA

Multifunctional Voice Terminal



- Intercom
- Radio Access
- Dual Homing
- Standard Interfaces (ISDN, IP)
- Graphics User Interface

TOMA—Total Integration (Internal & External) of User Voice Services Supporting VOIP Technologies.



TOMA S2



TOMA IP

TOMA

Multifunctional Voice Terminal



Thales' long-established experience in GUI (Graphical User Interface) and voice processing technology is embodied in the TOMA family of voice terminals.

The TOMA family comprises three basic configurations, SO, S2 and IP, available in vertical and horizontal variants and for wall or console mounting.

In addition to usual intercom voice services, TOMA comes with advanced functionality contributing to the full integration of voice services within the overall communication system. These include:

- Dual homing, required by resilient applications
- Radio access, for a fully-integrated communication system
- Dynamic configuration (directory, user login) for operational flexibility
- Plain to Cypher modes for security accreditation

TOMA voice terminals are fully operational and in service with several of the world's leading navies, providing advanced voice service within fully-integrated communication systems.

INTERCOM

- Point-to-Point
- Conference
- Broadcast
- Group Call
- Telephone

TECHNICAL SPECIFICATIONS

Voice Modulation

- TOMASO: PCM 64Kb/s
- TOMAS2: PCM 64kB/s
- TOMAIP: PCM 64kB/s

Simultaneous Communication

- TOMASO: 2
- TOMAS2: 16
- TOMAIP: 8

Call Initiation

- TOMASO: Single/Multi-action
- TOMAS2: Single/Multi-action
- TOMAIP: Single/Multi-action

Dual Homing

- TOMASO: No
- TOMAS2: Yes
- TOMAIP: Yes

Anti-feedback Contact

- TOMASO: Yes
- TOMAS2: Yes
- TOMAIP: Yes

Standard Signaling

- TOMASO: ISDN/SO
- TOMAS2: ISDN/S2
- TOMAIP: SIP or H323

Mounting

- TOMASO: Wall and console
- TOMAS2: Wall and console
- TOMAIP: Wall and console

Analog Outputs

- TOMASO: Built-in and external loudspeaker/headset
- TOMAS2: Built-in and external loudspeaker/headset
- TOMAIP: Built-in and external loudspeaker/headset

Analog Inputs

- TOMASO: Microphone
- TOMAS2: Microphone
- TOMAIP: Microphone

Digital Input/Output

- TOMASO: Analog I/O only
- TOMAS2: Ethernet 10Mb/s
- TOMAIP: Ethernet 10 Mb/s

Exposed Areas

- TOMASO: With specific box
- TOMAS2: With specific box
- TOMAIP: With specific box

Size (H x W x D)

- TOMASO: 10.50 x 5.60 x 3.15 inches (267 x 142 x 80 mm)
- TOMAS2: 10.50 x 5.60 x 3.15 inches (267 x 142 x 80 mm)
- TOMAIP: 10.50 x 5.60 x 3.15 inches (267 x 142 x 80 mm)

Environmental

- TOMASO: MIL-STD-461 (EMI) MIL-STD-810 (Shock and vibrations)
- TOMAS2: MIL-STD-461 (EMI) MIL-STD-810 (Shock and vibrations)
- TOMAIP: MIL-STD-461 (EMI) MIL-STD-810 (Shock and vibrations)

➤ Non-U.S. Government sales are subject to U.S. Government approval.
➤ Specifications are subject to change without notice.

Thales Communications, Inc.

22605 Gateway Center Drive, Clarksburg, MD 20871
Toll-Free: 1.800.258.4420 | Phone: 240.864.7000 | Fax: 240.864.7920
E-mail: naval.maritime@thalescomminc.com
Website: www.thalescomminc.com

